



BB 350R – BB 430R

BETONIERE A BICCHIERE - tipo rinforzato

BETONNIERES A CUVE BASCULANTE - type renforcé

TILTING DRUM MIXERS TOWBAR - reinforced type

HORMIGONERA DE TAMBOR BASCULANTE

remorcable con amortizacion chasis reforzado





Ammortizzatori barra di torsione
Amortisseur barre de torsion
Rubber suspensions
Ammortiguadores

BB 350R – BB 430R

BETONIERE A BICCHIERE - tipo rinforzato
BETONNIERES A CUVE BASCULANTE - type renforcé
TILTING DRUM MIXERS TOWBAR - reinforced type
HORMIGONERA DE TAMBOR BASCULANTE
remorcable con amortizacion chasis reforzado

CARATTERISTICHE TECNICHE DONNEES TECHNIQUES - SPECIFICATIONS - CARACTERISTICAS TECNICAS

		BB 350R	BB 430R
Capacità della vasca Capacité de la cuve Drum capacity Capacidad cuba	lt. ft	350 12 cu.	430 15 cu.
Resa per impasto Capacité malaxage Unmixed capacity (approx.) Capacidad efectiva hormigon	lt. ft	280 9 cu.	340 12 cu.
Potenza motore elettrico/diesel Puissance électrique/diesel Power electric motor/diesel Potencia motor eléctrico/diesel	230 V Hp 400 V Hp	1,5 2	1,5 2
Peso senza motore Poids sans moteur Weight without engine/motor Peso sin motor	Kg.	360	370
Pneumatici Roues Pneumatic tyres wheels Neumáticos		135 x 13	135 x 13
Lunghezza senza timone Longueur sans timon Length less towing bar Longitud sin timon	mm.	1100	1100
Lunghezza con timone Longueur avec timon Length with towing bar Longitud con timon	mm.	2150	2150
Larghezza Largeur Width Anchura	mm.	2000	2000
Altezza Hauteur Height Altura	mm.	1700	1700
Livello pressione acustica garantito Le niveau de puissance sonore Guaranteed noise level Nivel de ruido garantizado	LpAg	83,3 -85,7 dBA	